Wilhelmsen Ships Service

Last updated: 09/10/2026 12:56:27

SOX GUARD (CAUSTIC SODA 20-50%)

Product group: Product number: **912012**

SOX GUARD (CAUSTIC SODA 20-50%) reduces Sulphur Oxide (SOx) emissions in marine vessels to help your fleet stay compliant with Marpol Annex VI requirements.



Product information

SOX GUARD (Caustic soda 20-50%) reduces sulphur oxide (SOx) emissions in scrubber and EGC systems. Compliant with ASTM E291-18 standards, this product uses a 20-50% caustic soda to support SOx emissions reduction, assisting your vessels in meeting existing SECA (Sulphur Oxide Emission Control Areas) regulatory requirements.

Features

- Product available in liquid form and has concentration of 20-50% Caustic soda
- Designed to be used in Scrubber and Exhaust gas recirculation(EGR) systems
- Reduces SOx emissions in line with IMO Marpol Annex VI requirements
- Supplied in 1000 LTR IBCs or Tank Trucks depending on Port/Terminal restrictions

Benefits

- Trusted quality - ASTM E291-18 certified for reliability and performance
- SOx emissions management - ensures compliance with IMO Marpol Annex VI requirements

Specification

Physical properties

Appearance	Clear, Viscous liquid
Concentration	20-50%
Density [kg/m3]	1.210- 1.540
Form	Liquid

Approvals

ASTM E291-18 certified
IMO Marpol Annex VI compliant

Documents

SOX Guard Storage and Handling guidelines

SOx Guard (Caustic Soda 20-50%) flyer

SOX Guard Certificate of Conformity

SOX Guard IHM

Directions for use

Product is supplied in ready to use. Can be dosed directly to the scrubber and Exhaust gas recirculation(EGR) system.

Related products

Accessories

770190
CAUSTIC SPILL KIT

This page is printed from:
https://wilhelmsenstage.wilhelmsen.com/product-catalogue/products/marine-emission-control-solutions/sox-guard-caustic-soda-20-50/



© 2024 Wilhelmsen. All rights reserved.