

DETECTOR NEW GR230-HFC-4000 (SAMON: 37-625 W/SEN027)

Product group: 607 Product number: 708050

The SAMON fixed gas detector is designed to monitor and detect refrigerant gas leaks, within a concentration range of 0 to 4000 parts per million (ppm). Powered by a 230V supply, it is equipped with a metal sensor attachment that can be installed in the pressure relief valve of the refrigeration system.



Product information

To avoid the damage and dangers caused by refrigerant leaks, it is extremely important to follow the recommendations below to ensure that the leak monitoring system is functioning accurately.

- Replace visibly damaged monitors and detectors immediately.
- Check and test the detectors once every 12 months with diagnostic tool DT300

Required by Safety Standard for Refrigeration Systems, EN378:2016.

Replace sensor every 5 years

Under normal circumstances, the lifetime of the sensor in the detector is up to 5 years. As a preventive measure, we recommend that ship owners plan for sensor replacements when it is reaching 5 years in operation.

SAMON has developed a new sensor, SEN027 (SELF SENSE) that can be fitted in existing installations where SEN004 is used. The main feature of SEN027 (SELF SENSE) is its built-in filter that makes the sensor much more resistant against false alarms caused by dust, dirt, liquids, and aerosols. The change can be performed without any change in alarm settings, and calibration is recommended with DT300 and SM300-SELF SENSE sensor module.

For the 5-year sensor replacement, we recommend that ship owners use only SEN027 (SELF SENSE), for the entire leak monitoring system.

Features

- The detector is microprocessor controlled and displays the current operating status via LED's
- Three adjustable alarm levels with relay output (230V/5A)
- Alarm delay, selectable in four steps
- Manual or automatic reset on alarm
- Fail-safe function with built-in monitoring and power failure alarm
- Built-in self-test and service function
- Test terminal for service tools
- Robust non corrosive PC enclosure for installation also in aggressive environments

Benefits

- Safety of crew members** - round the clock monitoring and alarm. Alerts ship crew in case of emergency.
- Cost-saving** - Minimise refrigerant loss and reduce operating costs.
- Time-saving** - Product and spares can be delivered together with other marine products from WSS.
- Regulatory compliance** - Complies with major regulatory bodies such as F-gas Regulation, EPA, Marpol Annex VI, LR ECO Class notation and ABS ES Notation.
- Environmentally Friendly** - Enables early detection and minimise the release of harmful GHGs into the atmosphere.

Specification

General

Invent Hazard Material (IMO/IU) classification	NA
--	----

Documents

[SDoC and MD for IHM](#)

[Instruction Manual](#)

[Control and calibration of GR and GSR detectors](#)

Related products

Accessories

708039
SENSOR MODULE FOR DT300 - SM300-SELF SENSE (SAMON: 60-150)
708037
DIAGNOSTIC TOOL DT300 (SAMON: 60-130)

Spares

708041
NEW HFC SENSOR 0-4000PPM SELF SENSE (SAMON: SEN027)