Wilhelmsen Ships Service

Last updated: 24/10/2026 03:00:41

KLÜBERBIO AM 92-142 25 KG

Product group: **682** Product number: **210068**



KLÜBERBIO AM 92-142 is an environmentally acceptable high performance wire rope grease. Powerfully adhesive and water-resistant, it also has an excellent load-carrying capacity and anti-wear and anti-corrosion properties.

Product information

Steel rope wires in the marine and offshore industry are constantly exposed to harsh environmental conditions at sea. Sustained contact with salt water easily corrodes these wires, making them unsafe. KLÜBERBIO AM 92-142 helps extend the life of your wire by providing excellent load-carrying capacity and strengthening resistance to corrosion and other wear and tear. Reliable and high performing even with heavy loads and designed to help your wires last. KLÜBERBIO AM 92-142 was developed in close cooperation with Redaelli Tecna, a company of the global Teufelberger Group that specialises in steel wire roping. It is a recommended solution for both initial and relubrication of steel wire ropes. Importantly, KLÜBERBIO AM 92-142 possesses powerful adhesion strength to metal surfaces, good water resistance and temperature stability, reducing the risk of drip offs that can contaminate your deck or goods.

Features

- Compliant with the requirements for Environmentally Acceptable Lubricants (EAL) as defined by the EPA 2013 Vessel General Permit
- Good adhesion to metal surfaces
- Water-resistant
- Temperature stability
- Compatible with zinc coatings of galvanized ropes

Benefits

- Environmentally-friendly
- Protects your steel wire ropes from wear and tear
- Protects your steel wire ropes from corrosion
- No drip off that could contaminate your deck or goods
- Effective and economical in use
- KLÜBERBIO AM 92-142 is classified as an Environmentally Acceptable Lubricant (EAL) by the biodegradability, toxicity and bioaccumulation standards of the US Environmental Protection Agency and it contains over 60% renewable materials, serving our commitment to finding sustainable solutions for our environment .

Specification

General

Suggested Inventory Hazard Material classification	C-30

Physical properties

Biodegradability of the base oil, acc. to OECD 301 F, (within 28 days) [%]	≥60
Colour	Beige
Density at 20°C [g/cm³]	~ 0.98
Kinematic viscosity of the base oil, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 100 °C [mm²/s]	~ 22
Kinematic viscosity of the base oil, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 40 °C [mm²/s]	~ 140
NLGI grade, DIN 51818	2
Texture	Homogeneous, fibrous

Dimensions/Weight

Packing Size	25 kg

Technical data

Flow pressure of lubricating greases, DIN 51805-2, test temperature: -30 °C [mbar]	≤1400
Shelf life [months]	24

Performance data

Drop point, DIN ISO 2176, IP 396 [°C]	≥170
Lower service temperature	-30°C / -22°F
Oil separation, DIN 51817 N, after 7 d/40 °C	≤5% by weight
Upper service temperature	150°C / 302°F
Water resistance, DIN 51807 pt. 01, 3 h/40°C	0 - 40
Worked penetration, DIN ISO 2137, 25 °C [mm]	~ 275 x 0.1

Documents

SDoC and MD for IHM

Directions for use

KLÜBERBIO AM 92-142 is appropriate for use on steel wire ropes in the marine and offshore industry subject to harsh conditions, such as extreme hot or cold climates, constant exposure to seawater, and extreme loads.

You may use KLÜBERBIO AM 92-142 as initial lubrication during the production of the steel wires and/or for relubrication as a coating lubricant.

Apply KLÜBERBIO AM 92-142 by brush or automatic wire rope lubricators.

Follow the guidelines of the wire rope manufacturer w.r.t. the maintenance and inspection needs of your wire ropes.

Related products

Is consumable by

620006
VIPER MINI MK3 WRL KIT (25 KG CAP) FOR UNITOR™
620010
VIPER MID WRL KIT (25 KG CAP) FOR UNITOR™

This page is printed from:
https://wilhelmsenstage.wilhelmsen.com/product-catalogue/products/speciality-lubricants/kluberbio-am-92-142--25-kg/



Privacy notice and cookie policy
Data protection policy
Terms and conditions
Wilhelmsen whistleblowing channel
© 2024 Wilhelmsen. All rights reserved.