

# KLÜBERBIO LM 2-32 25 LTR CANISTER

Product group: **681**    Product number: **210050**

KLÜBERBIO LM 2-32 is a fully biodegradable, eco-friendly hydraulic fluid based on synthetic ester oils.



## Product information

Klüberbio LM2 oils are fully biodegradable, eco-friendly hydraulic fluids based on synthetic ester oils.

Klüberbio LM2 oils are intended for applications in mobile hydraulic systems, e.g. in the marine and offshore industries as well as for use in the building and water engineering sectors. They are also preferred in stationary hydraulic equipment operating in ecologically sensitive environments, e.g. in hydroelectric power plants and waterway locks

## Features

- Fully biodegradable, eco-friendly hydraulic fluids based on synthetic ester oils.
- Complies with the U.S. Environmental Protection Agency's requirements for classification as an Environmentally Acceptable Lubricant (EAL) in terms of biodegradability, toxicity and bioaccumulation standards according to Appendix A of the EPA's Vessel General Permit (VGP)
- Meets or even exceeds the minimum requirements of HEES oils according to ISO 15380

## Benefits

- Comply with the requirements for Environmentally Acceptable Lubricants as defined in Appendix A of the EPA 2013 VGP (Vessel General Permit).
- Fully biodegradable, non-toxic products reducing environmental impact in the event of leakage
- Facilitate start-up of hydraulic systems at very low temperatures due to very good viscosity-temperature behaviour and low pour point; can therefore be used in hydraulic systems with high temperature fluctuations.
- In addition, Klüberbio LM2 oils meet or even exceed the minimum requirements of HEES oils according to ISO 15380.

## Specification

## General

Invent Hazard Material (IMO/EL) classification	C-3
------------------------------------------------	-----

## Dimensions/Weight

Packing Size	25 LTR
--------------	--------

## Performance data

Anticorrosive properties on steel, DIN ISO 7120, method A, steel, 24 h/60 °C	no rust corrosion degree
Copper corrosion, DIN EN ISO 2160, 3 h/100 °C	1 - 100 corrosion degree
Flash point, DIN EN ISO 2592, Cleveland, open-cup apparatus [°C]	≥ 220 °C
Foam test, ASTM-D 892, ISO 6247, sequence I/24 °C [ml]	≤ 150/0 ml
Foam test, ASTM-D 892, ISO 6247, sequence II/ 93.5 °C [ml]	≤ 80/0 ml
Foam test, ASTM-D 892, ISO 6247, sequence III/24°C [ml]	≤ 150/0 ml
FZG scuffing test, based on DIN ISO 14635-1, A/8.3/90, scuffing load stage	≥ 12
Lower service temperature	-40 °C / -40 °F
Pour point, DIN ISO 3016 [°C]	≤ -45
Upper service temperature	110 °C / 230 °F

## Documents

[SDoC and MD for IHM](#)

## Directions for use

KLÜBERBIO LM2-32 is intended for applications in mobile hydraulic systems, e.g. in the marine and offshore industries as well as for use in the building and water engineering sectors. They are also preferred in stationary hydraulic equipment operating in ecologically sensitive environments, e.g. in hydroelectric power plants and waterway locks

## Physical properties

Appearance	clear
Biodegradability of the base oil, acc. to OECD 301 F, (within 28 days) [%]	≥ 60
Colour	green
Density at 20°C [g/cm <sup>3</sup> ]	approx. 0.915
Kinematic viscosity of the base oil, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 100 °C [mm <sup>2</sup> /s]	approx. 6.3
Kinematic viscosity of the base oil, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 40 °C [mm <sup>2</sup> /s]	approx. 32

## Technical data

Chemical composition, type of oil	ester oil
ISO viscosity grade of the base oil, DIN ISO 3448	32
Shelf life [months]	48
Vessel General Permit	fulfilled
Viscosity index, DIN ISO 2909	≥ 135

This page is printed from

<https://w.wilhelmsenstage.wilhelmsen.com/product-catalogue/products/speciality-lubricants/kluberbio-lm-2-32-25-ltr-canister/>