

Last updated: 13/08/2025 13:40:37

UNITOR HPC STATIONARY 6P

Product group: 435 Product number: 729406

The Unitor™ HPC Stationary 6P is a flexible pump station that is capable of supplying up to 6 simultaneous operators with pressurized water for high pressure cleaning. Dependant on the amount of operators performing high pressure cleaning on board the vessel, the Unitor™ HPC Stationary detects the line pressure drop and will automatically activate the number of pumps being required.



Product information

This product supersedes product no: 613806

Six pump stationary cold water unit for medium and heavy cleaning applications in maritime use.

The Unitor Stationary 6P model is for heavy cleaning applications with up to 6 users at same time.

Features

- Stainless steel frame and robust cabinet that ensure pumps and electronics are well-protected
- 6 pump system, each pump is equipped with four solid ceramic pistons
- Supplied with both cold and hot water inlet valves
- Smart pump control system with touch screen at the front panel
- Line pressures can be adjusted
- As water requirement drops, pumps will stop automatically
- Pumps operate on rotation to avoid excessive wear on single pumps
- The lower front panel can be opened for easy access to the pumps
- High level of serviceability, pumps and motors are quickly and easily removed

Benefits

- The pumps are installed on the frame with rubber dampers, and flexible connections to power and water
- Smart control system detects the amount of water required by the relevant number of operators and start the required pumps automatically
- Long life pump for intense applications
- Efficient operation and routine maintenance
- Up to 6 simultaneous operators

Specification

General

Invent Hazard Material (IMO/EU) classification	D-1
--	-----

Dimensions/Weight

Height [mm]	1800
Length [mm]	970
Weight [kg]	526
Width [mm]	1050

Technical data

Amperage [A]	87
Electrical phase	3
Frequency [Hz]	60
Ingress protection	X5
Inlet water temperature [°C]	70 maximum
Operating pressure [bar]	200
Power rating [kW]	53
Voltage [V]	440 mains supply
Water flow rate [l/min]	128,3 maximum

Documents

[SDoC and MD for IHM](#)

[Instruction manual](#)

Related products

Accessories

- 718577**
NOZZLE 06/25DGR. F/EXTENDABLE LANCE
- 621821**
DRAIN CLEANER F/HPC 67/HPC 61 HW/STAIONERY, 20M
- 659151**
EXTENDABLE LANCE 5.5MW/OUT NOZZLE
- 621938**
LONG REACH LANCE
- 546150**
DOUBLE LANCE 200CMLONG 064 NOZZLE
- 623595**
TAKE OFF VALVE 6402023 ACID PROOF 316
- 665158**
ERGO 3000 SPRAY GUN
- 659128**
POWERSPEED LANCE WITH 06 NOZZLE
- 623603**
TAKE OFF VALVE 6402024 CHR. PLATED BRASS
- 545327**
CHEM INJECTOR DETACHABLE
- 545335**
FOAMINJECTOR DETACHABLE
- 545434**
DOUBLE LANCE 10CMLONG 06 NOZZLE
- 545343**
FOAMLANCE 120CMLONG
- 546044**
WASHING BRUSH 235CMLONG
- 621896**
HOSE CART, MOBILE
- 682070**
UNIVERSAL.3000 LANCE 06 NOZZLE
- 546036**
COUPLING KIT ERGO 3000
- 718593**
NOZZLE 06/0DGR. F/EXTENDABLE LANCE
- 565861**
RUBBER NOZZLES (10 PCS) F/VSB 300
- 633995**
Q. COUPLING, MALE 3/4"
- 550030**
UNITOR HEAVY DUTY HOSE 250BAR BLUE 25M
- 550035**
UNITOR HEAVY DUTY HOSE 250BAR 25M
- 550040**
UNITOR HEAVY DUTY HOSE 250BAR 15M
- 770008**
UNITOR DYNAMIS/ PPE KIT 500 BAR
- 545025**
HOSE PROTECTION 1400MM Ø41 – 500 BAR WITH ADJUSTABLE STRAP
- 565853**
WATER SAND BLASTING LANCE F/VSB 300 03K
- 545640**
SUCTION HOSE&ROD F/VSB300
- 659110**
TORNADO LANCE 92CM WITH 06 NOZZLE

Consumables

- 571729**
HP WASH 25 LTR

