

NAVACLEAN 856 - ECOCLEAN 200 LTR

Product group: 030 Product number: 4000062

Navaclean 856 Ecoclean is a highly concentrated multipurpose water based cleaner for cargo tanks, which removes oil or dirt from any surfaces.



Product information

Navaclean 856 Ecoclean is a well balanced combination of natural citrus oil solvents, and advanced wetting agents, giving the product its power as a superior high quality water based cleaner and degreaser based on aliphatic/aromatic hydrocarbons, non-ionic and anionic surface active agents. It can effectively remove any oil and dirt from any surfaces.

Features

- Approved according to IMO MEPC.1/Circ. 590 and Marpol Annex V
- Promotes pleasant and healthy environment
- Safe for use to operating crew

Benefits

- Numerous marine cleaning & degreasing applications in engine room, galley, deck general cleaning
- Self splitting after cleaning
- Non flammable, low toxic
- Biodegradable
- Safe for use on zinc silicate coatings and most common metal surfaces.

Specification

General

Invent Hazard Material (IMO/EU) classification	C-49
--	------

Physical properties

Appearance	Colorless to pale yellow liquid
Density [g/ml]	1.0-1.1
Materials compatibility	May soften rubber. Limited application on epoxy coatings.
pH	7-8

Documents

[SDoC and MD for IHM](#)

[IHM & SDoc](#)

Directions for use

Tank Cleaning: Cargo tank cleaning after mineral, animal, fish and vegetable oils. Hydrocarbon freeing after cleaning with hydrocarbon solvent based cleaners like NAVACLEAN 888 – SEACLEAN, NAVACLEAN 818 – COLDWASH, etc.

Direct Injection Method: This will require a solution strength between 0.5 and 1%.

Recirculation Method: Use a solution strength between 0.5 and 2% The solution can be re-used until it is no longer effective.

Spot Cleaning: Depending upon the contamination NAVACLEAN 856 – ECOCLEAN should be sprayed undiluted or diluted down to 10% in water and allowed to soak on the area for 20 – 30 minutes. It must then be washed down with plenty water. The efficiency is increased by using warm water up to 60°C both for cleaning and when rinsing the surfaces.

** The maximum concentration is 10% and a maximum temperature of 60°C.

